



Hangzhou Risingsun Cable Co., Ltd

Applications:

Generally used for connecting alarm equipment such as sensors, control panels and other low voltage circuits.

Unshielded Alarm Cable

No of Cores	Construction	Material	Diameter(mm)	
2C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	7/0.254mm(22AWG)	7/0.20mm
	Dielectric	PVC	1.2mm	1.0mm
	Jacket	PVC/LSZH	3.6mm	3.2mm
4C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	7/0.254mm(22AWG)	7/0.20mm
	Dielectric	PVC	1.2mm	1.0mm
	Jacket	PVC/LSZH	4.2mm	3.8mm
6C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	7/0.254mm(22AWG)	7/0.20mm
	Dielectric	PVC	1.2mm	1.0mm
	Jacket	PVC/LSZH	5.1mm	4.2mm
8C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	7/0.254mm(22AWG)	7/0.20mm
	Dielectric	PVC	1.2mm	1.0mm
	Jacket	PVC/LSZH	5.5mm	4.6mm
10C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	7/0.254mm(22AWG)	7/0.20mm
	Dielectric	PVC	1.2mm	1.0mm
	Jacket	PVC/LSOH	5.9mm	5.0mm
12C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	7/0.254mm(22AWG)	7/0.20mm
	Dielectric	PVC	1.2mm	1.0mm
	Jacket	PVC/LSZH	6.5mm	5.6mm

Combination Type

No of Cores	Construction	Material	Stranded Conductor
4C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	2C×0.5MM2+2C×0.22MM2
	Dielectric	PVC	1.4mm+1.15mm
	Jacket	PVC/LSZH	5.0mm

Remarks: OEM/ODM are welcomed

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com