



# Hangzhou Risingsun Cable Co., Ltd

## Applications:

Wiring of fire alarms,Smoke detectors,Voice communications,Burglar Alarms

Fire protective circuits

## Unshielded Fire

## Alarm Cable

### Construction:

### Material

Conductor	Solid Bare Copper, Fully Annealed per ASTM B3
Insulation	Color-Coded, Polyvinylchloride (PVC)
Color-Code	Black/Red/Brown/Blue/Orange/Yellow/Violet/Gray
Jacket	Red Polyvinylchloride (PVC)
Voltage Rating	300V
Temperature Range °C	-20 to 75

AWG Size	No of Cores	Insulation Dia(mm)	Jacket Dia(mm)
22	2	1.14	3.10
22	4	1.14	3.56
22	6	1.14	4.25
18	2	1.52	3.80
18	3	1.52	4.05
18	4	1.52	4.45
18	5	1.52	4.90
18	6	1.52	5.33
18	8	1.52	5.84
16	2	1.80	4.35
16	4	1.80	5.13
14	2	2.30	5.33
14	4	2.30	6.30

**Packing** Coil Packing/ Paper spool/ Pastic Spool/Wooden drum/

**Remarks** OEM/ODM are welcomed

## HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com