




Hangzhou Risingsun Cable Co., Ltd

SF/UTP 4Pairs cable- Category 5E-PE

Description	SF/UTP CAT5e 4P-PE-TC60
Standard	ISO/IEC11801、TIA-568-C.2、YD/T1019
Carton Dimension	----
Cable Packing	Wooden Tray & Carton



Construction

Conductor	Solid-Bare Copper	Insulation colors	Blue,White/Blue	Rip Cord	yes
Conductor Dia.	0.50mm±0.005		Orange,White/Orange	Inner Jacket	PVC
Insulation	HDPE		Green,White/Green	Inner Jacket Color	Multiple
Insulation Dia.	1.0mm±0.03		Brown,White/Brown	InnerJacket Dia.	6.8±0.5mm
Drain wire	0.45mmTC	Shielded	AL Foil	Average Thickness	0.6±0.05mm
Braiding	0.1/16*7	Material	TC	Corverage	60%
Outer Jacket	PE	Outer Jacket Color	Black	Outer Jacket Dia	8.8±0.5mm

Electrical Characteristics

Frequency(MHz)	ATT (≤dB/100m)	NEXT (≥dB)	ELFEXT (≥dB)	RL (≥dB)	PS NEXT (≥dB)
1	2.0	65.3	63.8	20.0	62.3
4	4.1	56.3	51.7	23.0	53.3
8	5.8	51.8	45.7	24.5	48.8
10	6.5	50.3	43.8	25.0	47.3
16	8.2	47.3	39.7	25.0	44.3
20	9.3	45.8	37.7	25.0	42.8
25	10.4	44.3	35.8	24.3	41.3
31.25	11.7	42.9	33.9	23.6	39.9
62.5	17.0	38.4	27.8	21.5	35.4
100	22.0	35.3	23.8	20.1	32.3
Impedance(1to100MHz)		100±15 Ohm	DC Resistance 20°C(Ω/100m)		9.5
Capacitance (nf/100m)max		5.6	DC Conductor Resistance Unbalance		5.0
Capacitance unbalance(pf/100m)max		330	Insulation Resistance(MΩ/100M)max		500

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698

Fax: 86-571-63766808

Web:www.rscable.com