



Hangzhou Risingsun Cable Co., Ltd



KX6

Construction	Material	Diameter(inch/mm)	
Inner Conductor	Stranded Bare Copper	7/0.2	
Dielectric	Solided PE	0.146	3.7
First Shield	78% Copper Clad Aluminum Braid	/	/
Jacket	PVC/LSZH	0.240	6.10

Electrical Characteristics

Capacitance(pF/m)	67±2
Impedance(Ω)	75
Velocity of Propagation(%)	66.0
Retrun Loss(dB)	≥20
Shielding Effectiveness(dB)	>80
Spark Test(VAC)	4000
Operating Temp Range(°C)	-40 to 85

Attenuation (20 °C)

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
10	1.5	5.0
50	2.5	8.1
100	4.0	13.0
200	5.6	18.5
400	6.9	22.5
800	10.5	34.5
950	11.5	37.5
1000	13.7	45.0

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698

Fax: 86-571-63766808

Web:www.rscable.com