



# Hangzhou Risingsun Cable Co., Ltd



**P3 540**

Construction	Material	Diameter(mm)
Inner Conductor	Copper Clad Alumium	3.15
Dielectric	Foamed PE	13.05
First Shield	Seamless Aluminum tube(thickness)	0.61
Jacket	PE	15.49

## Electrical Characteristics

Capacitance(pF/m)	50±3
Impedance(Ω)	75±3
Velocity of Propagation(%)	87
Retrun Loss(dB)	≥20
Shielding Effectiveness(dB)	≥100

## Attenuation ( 20 °C )

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
5	0.14	0.46
55	0.47	1.54
83	0.58	1.90
211	0.95	3.12
250	1.03	3.38
300	1.13	3.71
350	1.23	4.04
400	1.32	4.33
500	1.49	4.89
600	1.64	5.38
750	1.85	6.07
865	2.00	6.56
1000	2.17	7.12

## HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698

Fax: 86-571-63766808

Web:www.rscable.com