



# Hangzhou Risingsun Cable Co., Ltd



**P3 750**

Construction	Material	Diameter(mm)
Inner Conductor	Copper Clad Alumium	4.24
Dielectric	Foamed PE	17.22
First Shield	Seamless Aluminum tube(thickness)	0.91
Jacket	PE	20.83

## Electrical Characteristics

Capacitance(pF/m)	50±3
Impedance(Ω)	75±3
Velocity of Propagation(%)	87
Retrun Loss(dB)	≥20
Shielding Effectiveness(dB)	≥100

## Attenuation ( 20 °C )

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
5	0.11	0.36
55	0.37	1.21
83	0.46	1.51
211	0.74	2.43
250	0.81	2.66
300	0.89	2.92
350	0.97	3.18
400	1.05	3.44
550	1.24	4.07
600	1.31	4.30
750	1.48	4.86
865	1.61	5.28
1000	1.74	5.71

## HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698

Fax: 86-571-63766808

Web:www.rscable.com