



Hangzhou Risingsun Cable Co., Ltd



RG213

Construction	Material	Diameter(inch/mm)	
Inner Conductor	Stranded Bare Copper	7/0.029	7/0.75
Dielectric	Solid PE	0.285	7.25
Shield	95% Bare Copper Braid	0.321	8.20
Jacket	PVC/LSZH	0.406	10.30

Electrical Characteristics

Capacitance(pF/m)	101.1
Impedance(Ω)	50.0
Velocity of Propagation(%)	66.0
Conductor DCR(Ohm/km)	5.6
Outer shield DCR(Ohm/km)	3.9
Return Loss(dB)	≥ 20
Shielding Effectiveness(dB)	> 80
Max Operating Voltage(RMS)	4000
Operating Temp Range($^{\circ}\text{C}$)	-40 to 85

Attenuation (20 $^{\circ}\text{C}$)

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
10	0.6	1.8
50	1.3	4.3
100	1.9	6.2
200	2.9	9.5
400	4.2	13.8
600	5.5	18.2
860	6.8	22.3
1000	7.5	24.5
1500	9.6	31.5
2000	11.1	36.4
3000	14.2	46.6
5000	19.60	64.2

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698

Fax: 86-571-63766808

Web:www.rscable.com